









Frost Clean

Turbo Mode











Anti-Rust Casting



Sleep Mode



SPECIFICATION:

| Type of AC | Split |
|--|----------------------------|
| Tonnage | 1 Ton |
| Cooling Capacity | 12000 BTU |
| Cooling Area | 90-120 sq feet |
| Rated Voltage & phase | 230V, Single |
| Rated frequency | 50Hz |
| Lowest running voltage | 170 Volts |
| Highest running voltage | 264 Volts |
| Withstanding Operating conditions | 20-47 °C |
| Cooling Capacity at rated condition | 3517 Watt |
| Cooling Power consumption in rated | 1260 Watt |
| Indoor side airflow (High) | 600 m3/h |
| Indoor side noise level (High/Mid/Low) | 43.95/40.97/39.14 dB(A) |
| Outdoor side noise level (Turbo/High) | Turbo-54.4/High-54.3 dB(A) |
| Dimensions (L*W*H) | 844 x 310 x 546 mm |
| Packing (L*W*H) | 900 x 372 x 610 mm |
| Weight: Net & Gross | 28±1 & 32±1 Kg |
| Indoor Fan speed (Turbo/High/Medium/Low) | 1300/1250/1100/1000 r/min |
| Display | LED Digit Display |
| Compressor Type | Fixed Speed |
| Motors Mechanical output Wattage | 25 W |
| Outdoor Fan speed | 850 R/min |
| Remote Operating Range | 8 Meter |



| Compressor type | Rotary |
|---|--------------|
| Type of internal device | Wall-mounted |
| Power consumption | 1.4 kW. |
| Refrigerant type | R-410a |
| Availability of connection route included | Yes |
| Track length | 3 m |
| Indoor unit weight | 10 kg |
| External unit weight | 30 kg |
| Sleep mode | Yes |
| Timer | Yes |
| Automatic on/off | Yes |
| Remote control (remote control) | Yes |

Warranty : 05 Years Compressor, 2 Years Parts & Service Warranty

